

# Agri-Vac

# 3510



**TOUGH TO BEAT IN THE LONG RUN**

# 3510



**3510 G**

### CLEAN UP

- Portable
- Efficient
- Versatile

The **3510 AGRI-VAC**, equipped with a WALINGA #510 SRT blower, can move up to 900 bu/hr (23 tonnes/hr). Weighing less than 1400 lbs. (635 kg), it can be used in the tightest corners to perform transfer, cleanup or loading operations. The 3510 moves grain on a cushion of air which maintains grain and seed quality.

The 3510 gas/electric model is mounted on a formed steel, three wheeled cart, with fork-lift pockets making it very simple to move into the smallest corner of your storage area. Available in 26.5 hp EFI gas, 15/20 hp electric, or with a 3 point hitch, it is the ideal unit for someone who needs a versatile and portable grain handling unit.

### SPECIFICATIONS:

	3510G (gasoline)	3510E (electric)	3510 3PH (PTO)
WEIGHT	1373 lbs (623 kg)	1373 lbs (623 kg)	900 lbs (410 kg)
HEIGHT	73" (185 cm)	73" (185 cm)	60" (152 cm)
WIDTH	34" (86 cm)	34" (86 cm)	47" (119 cm)
LENGTH	78" (198 cm)	78" (198 cm)	78" (198cm)
WHEELS	3 pneumatic (1 on swivel)	3 pneumatic (1 on swivel)	mounted on legs
BLOWER	#510 Walinga SRT (Sound Reduction Type), Super Hardened, Positive Displacement Blower	#510 Walinga SRT (Sound Reduction Type), Super Hardened, Positive Displacement Blower	#510 Walinga SRT (Sound Reduction Type), Super Hardened, Positive Displacement Blower
AIRLOCK	#1210 drop-thru cast iron	#1210 drop-thru cast iron	#1210 drop-thru cast iron
FRAME	1 piece formed steel	1 piece formed steel	1 piece formed steel
MOTOR/POWER	26.5 hp EFI gas kohler (19.8 KW)	15 or 20 hp (11,15 KW)	540 PTO (25 + hp)
STARTER	12 volt	"across the line"	not applicable
RECEIVER	18" dia. x 36" high (46 x 91 cm)	18" dia. x 36" high (46 x 91 cm)	18" dia. x 36" high (46 x 91 cm)
INLET	4" (100 mm) daffin couplings with plugs	4" (100 mm) daffin couplings with plugs	4" (100 mm) daffin couplings with plugs
OUTLET	4" (100 mm) daffin couplings with plugs	4" (100 mm) daffin couplings with plugs	4" (100 mm) daffin couplings with plugs



### BLOWER/AIRLOCK

- 510 Walinga SRT (Sound Reduction Type), Super Hardened, Positive Displacement Blower
- 12" x 10" (31x26 cm) Drop-Thru Airlock
- Combination belt/chain drive



**3510 G**

### OPTIONS

- Stainless steel hoses
- 3" (75 mm) rubber suction hose
- Discharge cyclone
- Remote shut off (gas model only)
- Super Hardened Airlock



**3510 E**

### ACCESSORIES

#### Nozzle:

- 4" Suction Nozzle
- 4" (100 mm) with cleanup head

#### Hoses:

- One 4" x 12' (100 mm x 3.65 m) rubber suction hose
- One 4" x 12' (100 mm x 3.65 m) galvanized discharge hose



**3510 3PH**

### CAPACITIES\*:

PRODUCT	Barley		Corn		Wheat		Beans	
	Bu/hr	Tonnes per hr	Bu/hr	Tonnes per hr	Bu/hr	Tonnes per hr	Bu/hr	Tonnes per hr
3510 G (26.5 hp EFI)	900	23	700	18	575	15	500	13
3510 E (20 hp)	700	18	650	17	500	13	450	12
3510 E (15 hp)	550	14	500	13	375	10	350	9
3510 3PH	700	18	650	17	500	13	450	12

\* Capacities based on using 12' (3.5m) suction line and truck loading kit. Barometric pressure, humidity, and condition of product will affect capacity. Due to continuous product development, specifications may improve without notice.

## WALINGA.COM

### Head Office

R.R. #5,  
Guelph, Ontario  
Canada N1H 6J2  
Tel: 519.824.8520  
Tel: 888.925.4642  
Fax: 519.824.5651

### Michigan

1190 Electric Ave.  
Wayland, Michigan  
USA 49348  
Tel: 616.877.3470  
Tel: 800.466.1197  
Fax: 616.877.3474

### Manitoba

70 3rd Ave. N.E.  
Box 1790  
Carman, Manitoba  
Canada R0G 0J0  
Tel: 204.745.2951  
Fax: 204.745.6309

### Ontario

938 Glengarry Cres.  
Fergus, Ontario  
Canada N1M 2W6  
Tel: 519.787.VACS (8227)  
Fax: 519.787.8210

### Australia

Customvac Australia  
24 Molloy St.  
Toowoomba Qld 4350  
Australia  
Tel: 1800 242 699

